Cyclone Rotary Surface Cleaner The "Cyclone" rotary surface cleaner can be used with most hot and cold water washers. It reduces overspray and zebra striping. Great for warehouse floors, sidewalks, pool decks, parking lots, etc. • 4-10 GPM • 2000 - 3500 PSI • 200°F · Polyethylene housing · Collapsible handle • Pneumatic tires · 20" diameter surface cleaning • Up to 5 gpm · Weight: 35 lbs

Part No. 30-587 Description "Cyclone" Surface Cleaner

Whisper Wash Flat Surface Cleaners

Restaurants

Gondolas

Stadiums

- · Saves labor, fuel & water
- · Eliminates overspray and zebra striping
- · Use with conventional pressure washers
- · Use with cold or hot water

Applications:

- Service Stations
- Pool & Patio Decks
- Warehouse Floors
- · Loading Docks
- · Parking Lots

- - School Yards
 - And lots more!! •
- · Marina Docks

•

The "Maxima 36"

· Portable Breakaway Handle

Description

343636 Maxima 36

Ground Force

· Flip and fold handle · Choice of 2 or 4 nozzles · Rebuildable swivel

- 212°F
- 4-10 GPM
- 2500 RPM
- Dimensions:

Part No.

212°F

• 4-10 GPM

· Weight 29 lbs

- Cover: 36" Handle: 77
- Weight 37 lbs



Whisper Wash Flat Surface Cleaners - continued

The "Big Guy"

- · Powder coated aluminum housing
- · Oversized, self-lubricating twin thrust bearings
- · Choice of 2 or 4 nozzles
- 10" pneumatic tires, 4" caster
- · Crafted with durable stainless steel & aircraft aluminum
- 212°F
- 4-10 GPM
- Dimensions: 28" x 44" x 12"
- Weight 48 lbs

Part No. Description

Whisper Wash Big Guy 2 Nozzles 343606 343607 Whisper Wash Big Guy 4 Nozzles

The Classic

- · Portable breakaway handle
- ABS Housing
- 2" nylon brush
- 212°F
- 4-10 GPM
- Dimensions: 19" x 77" x 12"
- Weight 28 lbs



Part No. Description

343605 Whisper Wash Classic

The Ultra Clean WW

- ABS Housing
- · Four 3" casters
- · Powder coated handle
- 185°F
- 3-6 GPM
- 2500 RPM
- Dimensions: 19" x 43" x 9"
- Weight 23 lbs



Description Part No. 343604 Whisper Wash Ultra Clean WW

Description Part No.

• Dimensions: 24" x 60" x 9"



- Driveways Sidewalks
- 2500 RPM Public Facilities

· Balanced spray bar

Quick connection

2,000 to 4,000 PSI



343603 Whisper Wash Ultra Clean HC

Part No.

• 185°F

• 3-6 GPM

Repair Kits				
092105	Seal Kit; Classic, Big Guy & Ground Force			
092108	Seal Kit; Ultra Clean			
092109	Swivel Kit; Ultra Clean			
092110	Swivel Kit; Classic, Big Guy & Ground Force			
251119	2.5 x 25° 1/4" nozzle fits All Models			

Water Broom 16"



- 4000 PSI
- · Fits any 1/4" wand
- Requires (4) 1/4" nozzles and wand

Part No.	Description
343615	Water Broom 16"

Water-Sweepers



Excellent for sidewalk or concrete floor cleaning. Controls spray deflection. · Rolls on four wheels · Plastic cover with brush spray breaker

Uses four Brass 1.5 x 80° V-jet nozzles (254620, below) · Rated for 1,500 PSI w/ Brass nozzles · Rated for 2.500 PSI w/ SS nozzles (non-hardened)

• 4000 PSI 6 5lbs

• 250°F



- 4000 PSI 2lbs
- 250°F Inlet Ports: .
- 3/8" NPTF

Swiss engineered with high RPM Swivel features reinforced self-lubricated stainless steel ball bearings and dual spring based carbide seal bushings for long-lasting operation under tuff conditions.

Ideal for Pressure Washer Contractor to clean Walls, Ceilings, Public Facilities, Tile Floors and other hard to reach areas.

Duct Cleaner

Mosmatic Turbo

Delivers high-pressure performance with low maintenance for any hot or cold pressure washer. Completely stainless steel design makes this the toughest sur-

face cleaner available in the pressure cleaning market.

Designed as an accessory for use with high pressure pumps or pressure washers. Cleans Ducts, Chutes, Vents, Restaurant Exhausts, Tanks, etc.

Self rotating and feeding stainless steel triple bearing system for constant easy turning. Nozzle holders are 1/8" NPTF. Nozzles are sold separate.

Part No.	Description	PSI	
411171	Turbo Cleaner	4000	
411172	Toggle Joint KGK	4000	
411156	Duct Cleaner TXR-2s, Adjustable	4000	
411155	Duct Cleaner TXR-2s, Fixed	4000	

Mosmatic Gun Swivel

Mounts to your high pressure gun or lance for an easy turning, low maintenance gun swivel



- 4000 PSI 250°F
- 30 RPM



Part No.	Description	
421057	1/4" MPT / 1/4" FPT Gun Swivel	
421056	3/8" MPT / 3/8" FPT Gun Swivel	

Part No. Description PSI 343602 ST-95 Water Sweeper (brass) 1500 254620* Nozzle 1/8" #1.5 x 80° (SS) 2500

*Longer lasting replacement nozzle

Thunderdome Flat Surface Cleaner

A "Must Have" tool for every serious mobile cleaner.





- Premium Quality Mosmatic Swivel
 Steel 1/4" Q.C. Inlet to Guns, Lances,
- Injectors, Filters or other accessories • Height 7.5" - OD 14.5"
- Light Weight 3.2 lbs
- Size 5 Nozzle Equivalent
- Two Standard
- 1/8" 3.0 x 40° replacement nozzles
 2.5 GPM @ 1000 PSI
- 2.5 GPIN @ 1000 PSI
- 4.0 GPM @ 2500 PSI 4.4 GPM @ 3000 PSI

• 4.4 GPM @ 3000 P

Part No.Description343610Thunderdome Base Unit092175Repair Kit

NOTE: Price does not include gun-hose-lance-etc.

Oil-Fired Hot Box

Add hot water cleaning economically! Portable water heater add-on for existing cold water pressure washers. Quick Connect to cold water washer, supply fuel and power to Euro-Heat for hot water cleaning applications - USE ONLY WHEN NEEDED and keep the convenience of the portable cold water washer.




- 3000 PSI
- Quick Hookup 3/8" QC inlet/outlet
- · Easy service access to burner parts
- Efficient vertical combustion configuration
- Diesel, Kerosene, #1 Heating Oil
- 10" Easy roll tubed pneumatic wheels
- 5 gallon plastic fuel tank
- Compact size 37" W x 27" L x 39" H
- 36' Ground Fault Interrupter plug
- Thermostat temperature control

Part No.	Description
HR-5030D	5 GPM / 3000 PSI - 120V


Goff's Curtain Walls


Build a Power Wash Cell to meet your needs. Goff's Curtain Walls[™] increase useable floor space while controlling overspray, contaminants, climate, and noise levels. Curtain Walls[™] glide easily on steel track and dual-wheeled rollerhooks. Made from a combination of 14-oz. heavy-duty, reinforced vinyl and double-polished 20-mil clear PVC material. Reinforced hems and chain-weighted lower hems add durability. Hook and loop fasteners on side hems attach to adjacent panels. Meet NFPA-701 requirements for flame retardancy. Curtains are also rot and mildew resistant. Standard model has a white vinyl top, clear PVC center, and blue vinyl bottom.





- #2 Brass tooth grommets on 1' centers
- 14 oz. reinforced vinyl white top section
- All seams double locked stitched
- Hook & Loop Fasteners allow adjacent panels to be easily attached to one another
- 20 mil. double polished clear window
- All sections joined together using mildew/ rot resistant thread
- 14 oz. reinforced colored vinyl section
- (your choice of over 12 different colors)
- Chain weighted lower hem





Part No.	Description	PSI	
Single			
681135	6' width x 8' high	1500	
681136	6' width x 9' high	1500	
681134	6' width x 10' high	1500	
681133	6' width x 12' high	1500	
681083	12' width x 8' high	1500	
681084	12' width x 9' high	1500	
681089	12' width x 10' high	1500	
681082	12' width x 12' high	1500	
681088	24' width x 8' high	1500	
681085	24' width x 9' high	1500	
681086	24' width x 10' high	1500	
681087	24' width x 12' high	1500	
Station			
681137	2-sided x 8' high	1500	
681146	2-sided x 9' high	1500	
681140	2-sided x 10' high	1500	
681143	2-sided x 12' high	1500	
681138	3-sided x 8' high	1500	
681147	3-sided x 9' high	1500	
681141	3-sided x 10' high	1500	
681144	3-sided x 12' high	1500	
681139	4-sided x 8' high	1500	
681148	4-sided x 9' high	1500	
681142	4-sided x 10' high	1500	
681145	4-sided x 12' high	1500	

includes hardware, track & rollers (white top, clear center & blue bottom panel) All 2,3 & 4-sided stations are 12' wide x 24' long (see diagram above)

Industrial Sandblaster

Working	Flow: 4 GPM at 3000 PSI	
-	up to 8 GPM at 5000 PSI	

- · Carbide Sand Nozzle
- 25' Suction Hose
- Use 1/4" meg 5° Spray Tip
- · Tips not included, buy separately

Part No.	Description	
391510	Sandblast Kit	
092157	Carbide Sand Nozzle	
251159	4.0 x 5° Tip	
251198	5.0 x 5° Tip	
251221	5.5 x 5° Tip	
251237	6.0 x 5° Tip	
251256	6.5 x 5° Tip	

Dual Chemical Systems



- · New deep-ribbed Yellow casing, stays flexible even in cold temperature
- Hose assembly complete with gun and amphenol connectors pre-wired
- Fully compatible with Power Blaster, Two-Step, Chemex and most other cold water dual chemical systems

Part No.	Description				
Complete H	Complete Hose Assembly				
285116	80' R2 Electric (5 wire)				
285120	100' R2 Electric (5 wire)				
Lance Attac	hment Parts				
285136	Female Receiver				
285137	Male Lance Swivel				
285138	Retainer Nut				
Complete R	emote Gun Unit				
285125	Gun, Electric				
Remote G	un/Hose Parts				
285135	Gun Housing				
285139	Switch P/B				
285140	Switch, Chemical				
285142	Switch Plate				
285144	O-ring, Nipple (2 req'd)				
285145	O-ring, Nipple (Bags of 50)				
285175	Swivel Adapter				
285177	Cord Grip				
285181	Oetiker clamp				
285187	Switch – Push Button Trigger				
285189	Toggle, DPDT (Trig) On/Off/On				

Professional Sandblast Head • 10 GPM

• 3500 PSI



• 1/4" FPT water inlet

- Sand probe weight 6 oz, length 16"
- 200°F
- · Carbide sand nozzle
- weight 13 oz

е	•	Head
0		

Nozzle Size			Nozzle Size	
3.5	391631		5.5	391635
4.0	391632		6.0	391636
4.5	391633	-	8.0	391637
5.0	391634			

Part No.	Description	
391640	Sand Probe	
101041	1/0" ID Dolubroid T	

1/2" ID Polybraid Tubing, 25' 121041

Carbide Nozzle Industrial Grade Sandblast Kit -



A Venturi orifice creates a uniform blast pattern, doubles sand velocity and produces up to 45% more work with 20% less sand.



Kit contents: Sand head w/ carbide nozzle, 20" lance, Sand probe, 13-1/2' sand hose, Sand flow regulator valve.

- · Solid Carbide blast nozzle
- Venturi orifice design
- · Volume control sand feed valve
- Up to 3500 PSI

Kits			 Up to 750 	lbs of sand	l per hour
		Orifice Size		Orifice Size	
		4.0	391554X	6.0	391556X
		4.5	391553X	7.0	391557X
		5.0	391555X	10.0	391560X
Solid Carbide Nozzle only	Part No. 086941	5.5	391550X		
,					

Tip-Jet Nozzles for water nozzle replacement or for system volume changes

Orifice Size		Orifice Size	
3.0	253316	6.5	253375
4.0	253330	7.0	253383
4.5	253338	7.5	253392
5.0	253346	8.0	253400
5.5	253355	9.0	253415
6.0	253365	10.0	253456

Foot Controlled Pressure Valve

SUTTNER W

Operators of sewer and tube cleaning equipment need both hands free to feed or retract the hose in the sewer line. Foot operated valve allows hands-free control.



- Inlet 3/8" outlet 1/4"
- · Brass body Stainless steel valve
- · Steel cover for safety
- Up to 12 GPM
- Up to 5000 PSI

Part No.	Description	PSI	
344200	Sewer Cleaner Foot Valve	3000	
342024*	Foot Valve w/ ST-2305	5000	
089006	Repair Kit - Foot valve		
089850	Repair Kit ST-2305		
4-0193	Kit, 25' Hose, #4.5 Nozzle, F	oot Valve	
*Heavy gauge steel construction for durability and stability			


Tube Cleaning Nozzles



The reverse jets on the fixed and rotary nozzles pull the hose through the tube or sewer line and blast debris from line or tube walls. Fixed nozzles also have forward orifice to blast blockage out of the way.



Part No.	Description	Size	
373024	1/8" Nozzle (back jet only)	4.5	
373023	1/8" Nozzle	5.5	
373027	1/4" Nozzle	4.5	
373025	1/4" Nozzle	5.5	
373026	1/4" Nozzle	6.0	
373029	1/4" Nozzle	7.5	
373028	1/4" Nozzle	8.0	
373032	1/4" Nozzle	12	
373038	3/8" Nozzle	4.0	
373037	3/8" Nozzle	5.5	
373039	3/8" Nozzle	8.5	
373036	3/8" Nozzle	12	
373035	3/8" Nozzle	14	



- Clears clogs and flushes out lines
- 4200 PSI



- · Rotating sewer nozzle
- · Adds extra agitation
- 3000 PSI
- Back Jet Only

373027	1/4" Nozzle	4.5	
373025	1/4" Nozzle	5.5	
373026	1/4" Nozzle	6.0	
373029	1/4" Nozzle	7.5	
373028	1/4" Nozzle	8.0	
373032	1/4" Nozzle	12	
373038	3/8" Nozzle	4.0	
373037	3/8" Nozzle	5.5	
373039	3/8" Nozzle	8.5	
373036	3/8" Nozzle	12	
373035	3/8" Nozzle	14	

Part No.	Rotating Nozzle	Size	
373062	1/8"	5.5	
373061	1/4"	5.5	
373064	1/4"	8.0	

5.5

373040	1/4"
	Duct CInr*

*Duct Cleaner jet to sides instead of reverse

Stainless Steel Sewer Nozzles



41	00	PS		
<u> </u>				 •

- Corrosion Resistant Stainless steel
- One Forward Orifice
- · Three Rear Orifices

Part No.	FPT	Size	
373075	1/8"	5.0	
373076	1/8"	5.5	
373077	1/8"	6.0	
373078	1/4"	6.5	
373079	1/4"	7.0	
373080	1/4"	9.5	

Sewer Hose

SUPER FLEXIBLE SEWER LINE HOSE Hose and couplings have small outside diameter, allowing hose and nozzles to fit through sewer line. Sewer line has



Super Tough poly-ether cover over ultra-flexible nylon tube. (1/8" sewer nozzle and hose will operate through many 1-1/2" lines.) (Nozzles not included.)

> • 160°F · Nylon tube, poly-ether cover

Part No.	Description	
1/8" hose -	- 4800 PSI, 1/4" inlet/1/8" outlet	
150960	1/8" x 25'	
150963	1/8" x 50'	
150964	1/8" x 100'	
1/4" Hose	- 2600 PSI, 1/4" inlet/1/4" outlet	
150968	1/4" x 50'	
150970	1/4" x 100'	
1/4" Hose	- 4400 PSI, 1/4" inlet/1/4" outlet	
150972	1/4" x 50'	
150973	1/4" x 100'	

ST-35 Pit Boss Sludge Sucker SUTTNER W

Sludge Sucker uses a high pressure water stream (1000-3000 PSI) to suck the sludge off the bottom of pits or tanks and eject it through a 1-1/2" (15' long) hose to a disposal tank.



The base unit attaches to the end of a pressure washer lance with a quick coupler for extension to the bottom of the pit. Comes standard with a #5.5 x 0° tip for suction/power ejection.

- Uses standard 1/4" MPT nozzle
- · Easy to change for different plumbing system flows and pressures

Part No.	Description		
376137	ST-35 Pit Boss, 5.5 Nozzle/ 15' Hose		
376126	(Base unit only)		
*w/o hose, nozzle or quick coupler (3/8" inlet port)			

**See nozzle chart on page 30



Part No.	Description	
449339	Drum Plug Wrench	
118400	Lid-Off	
118404	Funnel, 7" x 10"	
118407	3/4" Faucet	
118408	2" Faucet	
Load Cinch	er Tie Downs	
249938	7/8" x 5-1/2' (Non-Ratchet) "Quick Lock"	
249939	1" x 15' (Ratchet) "Tight Lock"	

Fiberglass "Super Handles"

- Tough durable lightweight
- No cracking splintering
- No kinks dents
- · Safer around electrical hazards
- Easy-Twist cam lock extension

Part No. Description

Super Hand	les	
306864	48" Length (4 ft)	
306865	60" Length (5 ft)	
306866	72" Length (6 ft)	
Super-Exter	nsion Handles	
306868	4 ft to 8 ft Ext	
306869	6 ft to 12 ft Ext	
306870	8 ft to 16 ft Ext	
075271	Threaded Adapter	

• Super heavy-duty aluminum

Standard 3/4" Acme thread fits:

Brooms, brushes, utility tools

• Optional reduction adapter for 3/4"

alloy threads

to Acme standard

Brushes

Rotating Brush - Natural Bristle (soft) used for painted surfaces. Nylon Bristle (stiff) used for removing scum and grime on fiberglass boats, etc.



- Internal nozzle = size 20
- 8 GPM

Part No. Description

Brush Unit Complete

306925 Natural **306935** Nylon

Replacement Brushes

306927 Natural

306937 Nylon

Truck Wash Brush



- Flag-tipped
- Firm bristle
- Poly block "Flow-Thru" head
- ACME thread for Super Handles, Flow-Thru lances or broom handles
- Trailer Brushes (2-1/2" Bristle w/Bumper)

Part No.	Description	
306800	2-1/2" x 10"	
306818	2-1/2" x 18"	
306824	2-1/2" x 24"	
306860	60" Flow Thru Lance*	

*with Acme Thread & Garden Hose Attachment

Deck Scrub Brush – Over / Under - Unique Heavy-duty Scrub Brush with Multi-Level/Angle.

- Trimmed for cleaning hard-to-reach areas
 - 10" molded polypropylene foam block does not warp or absorb water
 - Stiff polypropylene bristle for aggressive cleaning
 - Excellent chemical resistance
 - Use with threaded handle
 - Not a Flow Thru

Part No.Description306812Deck Scrub Brush

Tractor Brush - Soft for gentle cleaning of fine finishes.



Part No.	Description	
306802	Flag Tip Window 10"	
306810	"Extra-Soft" 10" w/ Bumper	

Compact Foamer



Generates a high density clinging foam for extended dwell time to increase chemical action



- Stainless steel. 1 to 5 GPM aluminum and brass • 195°F
- 5" long, 1" diameter
- 4 and 6.5 nozzle
 - included

Part No. Description 344022V 1/8" F Inlet 344023V 1/4" F Inlet

NOTE: Most cleaning chemicals perform best when applied at 120° - 150°F and can be applied as a foam by adding a foaming agent. See your chemical supplier to obtain the correct product.

Foam Cannon

344030

The Ideal Foam Generator Application Accessory meters the foaming chemical for customized foam type and applies the foam to match the application.

-	
-	 Stainless Steel 1.5mm orifice (#5.5 nozzle equivalent)
	 Brass meter valve
	 3000 PSI
-	High impact glass-filled body
Part No.	Description

- 4.8 GPM
- SS Foam Turbulator
- 176°F
- 1/4" FPT lance connect

• 2500 PSI

Foam Cannon/ Injector

344032	Foam Cannon/ Injector/Bottle	
		Î

Air Power Sprayers · Pump-up style · Heavy-duty plastic sprayers for chemical applications • Both models have Adj. Nozzle - from mist to solid stream · 2 gallon unit has 2' hose and hand trigger · Excellent chemical resistance · Locking hand pump handle serves as carrying handle

Part No.	Description	
118842	Thumb Button 3 Pint	
118835	2 Gallon Sprayer	

Siphon Pumps

Siphon liquids from higher to lower levels. Simply pump the bellows a few times to prime and start flow. Loosen air lock to stop.



- Drum pump fits 15, 30 & 55 gallon drums
- Fit 2" bung opening
- Excellent for: Alkaline & acidic chemicals, diesel fuel, & oils
- Not for use with solvents!

Part No.	Description	
118431	Super Duty "PE/PVC" 7 GPM	
118429	Red Hex Head (Heavy-duty)	
118423	Red Head (Standard duty)	
118420	Pail Pump (5 Gallon)	

Drum / Tank Pump - Crank Type

Chemical-resistant, lightweight pump, ideal for dispensing chemicals, pesticides and oils. Polypropylene for most alkalies, dilute acids, pesticides, and most oils & solvents. Ryton for extremely aggressive acids, aromatic and aliphatic hydrocarbons.





· Viton seals

· Polypropylene gasket

- 2" bung adapter
 - Outlet 3/4" barb 2 piece
 - 47" suction tube
 - · Weight 2.6 lbs

Part No.	Description	
118435	Polypropylene Pump (Standard)	
118438	Ryton Pump (Deluxe)	
076975	Replacement Handles	

Teflon® Thread Sealing Tape



 Big 1/2" x 520" roll Mil - spec #T27730

Part No. Description 118905 Thread Sealing Tape

Thread Lock Products



- Direct replacement for LocTite[®] and Fel-Pro™ products
- ND[™] anaerobic adhesives are liquid materials that cure to a solid, chemical-resistant plastic state when air is not present
- Excellent lubricant; prevents corrosion and fretting

Part No.	Lo	ocTite® Equiv	Bottle Size	
112350	Nut Grade™	242	10 ml	
112352	Nut Grade™	242	50 ml	
112354	Nut Grade™	242	250 ml	
112360	Stud Grade™	271	10 ml	
112362	Stud Grade™	271	50 ml	
112367	Penetrating Adhesive (Sealant)	290	10 ml	

Nut Grade™ and Stud Grade™ are trademarks of the Oakland Corp.LocTite® is a registered

trademark of the LocTite Corp.

Gloves - Industrial Duty

Industrial Grade Gloves for most industry needs chemical/ heat/ abrasion/ laceration protection.



116114 Black, 14" PVC Glove lined with cotton for the most demanding chemical handling. Resists alkalines, acids - even works well as a sandblasting glove.

116105 Gray - Split Cowhide work gloves, 2-1/2" gauntlet unlined – Great general purpose work glove.

Part No.	Description
116105	Gray Roughout
116114	Black PVC

Rain Suit - 2 Piece



- Heavy-duty 2-ply laminated vinyl (25 mil)
- · Jacket & pants
- · Bright safety yellow
- Vented for air flow

Part No.	Description	
116100	Large	
116101	Extra Large	

Amazing Pocket Reference - 3rd Edition

A ton of information in a 5 oz book!



Part No.

- Air & gases
- Automotive
- Chemistry
- Electrical
- · Physical constants
- Math
- 3350 conversion factors
- · Plumbing & pipe Over 20 other
- subject areas

Description 449015 Pocket Reference

Shipping Tape & Dispenser

Big 2" x 110 yard rolls of clear. Biaxially-oriented polypropylene for secure packages.

